

OE14-110/111



KONGSBERG



January 2016

COMPACT COLOUR CCD CAMERA

- **Rugged**
- **Compact dimensions**

The Kongsberg Maritime OE14-110 (PAL) and OE14-111 (NTSC) Low Cost Mini Colour Camera utilises the latest solid state sensor technology to provide a cost-effective, miniature colour camera with excellent light sensitivity and image definition.

The units are robustly constructed with a tough marine grade aluminium alloy pressure housing rated to 3,000 msw operation as standard. Alternative housing materials and depth ratings are available.

Very compact dimensions make the OE14-110/111 ideally suited for ROV manipulation and tooling applications.

Auto shuttering, together with a wide AGC range give excellent light compensation at minimum cost. The lack of any moving parts and robust construction makes the camera extremely resistant to shock and vibration.

Applications

- ROV Manipulation
- ROV Tooling
- General Observation
- Diver

TECHNICAL SPECIFICATIONS

Performance

Horizontal Resolution	460 TVL/PH (OE14-110) 470 TVL/PH (OE14-111)
Light Sensitivity	100 mV video at 15×10^{-3} lux faceplate 350mV video at 70×10^{-3} lux faceplate
Minimum Scene Illumination	1 lux
Signal to Noise Ratio	>52 dB (weighted)

Electrical

Scan Standard	625 lines 50Hz PAL (OE14-110) 525 lines 60Hz NTSC (OE14-111)
Sensor Elements	765 (H) x 582 (V) (OE14-110) 768 (H) x 492 (V) (OE14-111)
Video Output	1V pk - pk composite video into 75Ω
Power Input	12 - 24V dc, 250mA (max)

Optical

Lens	2.5mm F/2.0
AOV in water	Horizontal: 61° Vertical: 46° Diagonal: 73°
Iris Control	Fixed electronic iris with automatic shutter
Focus Range	Fixed focus, 115mm to infinity

Mechanical

Dimensions	Diameter: 40mm Length: 99mm (excl. connector)
Weight	In air 0.25Kg, in water 0.15Kg
Housing Material	Aluminium alloy HE30T6 to BS1470, Hard Anodised Black
Connector	BH-4M

Environmental

Operating Depth	3,000 msw (other depth rated housing options are available)
Temperature	Operating: -5 to 40°C , Storage: -20 to 60°C
Shock	30G peak acceleration, 25ms half sine duration, on all three axes
Vibration	10G, from 20 to 150Hz on all three axes
Electromagnetic Compatibility	BS EN 50081-1: 1992 Emission and BS EN 50082-1: 1992 Immunity

Specifications subject to change without any further notice

OE14110_Datasheet_A4 / Rev.B

KONGSBERG MARITIME

Telephone: +44 1224 226500
E-mail sales: km.camsales.uk@kongsberg.com
E-mail support: km.camsupport.uk@kongsberg.com

www.km.kongsberg.com



KONGSBERG